



Unilong Industry Co., Ltd

Add: No.2000 Shunhua Rd, High-Tech Zone , Jinan City, Shandong Province, China

Technical Data Sheet

Product Name: Ethylene Glycol Monoethyl Ether

CAS: 110-80-5

Packing: packed in iron drum, 190 kg/barrel

Chemical composition:

Items	EE
Appearance	Transparent colorless liquid
Purity $\geq\%$	99.5
Moisture $\leq\%$ (Premium grade)	0.1
Moisture $\leq\%$	0.2
Acidity (As HAC) $\leq\%$	0.005
Distillation range (760mmHg °C) (Premium grade)	133.5~ 138.0
Specific Gravity % (d4 ²⁰)	0.9294 \pm 0.005
Color(Pt-Co)	15

Application: widely used as a paint solvent. Because of water dissolving capacity is big, easy to occur when used alone emulsifying phenomenon, so often mixed with other solvents. Mainly used as nitro paint solvent. Other detergent is also used as a car engine, electric insulation with siloxane modified polyester paint solvents, printing ink vehicle, vitamin B12 recycling solvent refining, cortisone acetate solvent, jet fuel additive, automobile brake oil, leather colorants, emulsion stabilizer, etc.

Storage: store in a cool, ventilated, dry place, according to the dangerous chemical transportation